



IFDR.E362522 - Low-voltage Lighting Systems, Power Units, Luminaires and Fittings

Note: We are enhancing our systems and you may notice duplicate entries/missing/outdated data. During this interim period, please contact our Customer Service at <https://www.ul.com/about/locations>.

Low-voltage Lighting Systems, Power Units, Luminaires and Fittings

FLEXFIRE LEDS INC

E362522

3554 Business Park Dr., Suite F
Costa Mesa, CA 92626 United States

LED low voltage luminaires, Model(s): CB-RGB(b)(c), CB-RGBXX(a)(b)(c), CB-XX(a)(b)(c), IUB-XX(a)(b)(c), UB-AS-XX(a)(b)(c), UB-AS-XX-24V(a)(b)(c), UB-AT1-XX-12V(a)(b)(c), UB-AT1-XX-24V(a)(b)(c), UB-AT1-XX-48V(a)(b)(c), UB-AT2-XX-12V(a)(b)(c), UB-AT2-XX-24V(a)(b)(c), UB-AT2-XX-48V(a)(b)(c), UB-CRI-XX(a)(b)(c), UB-DS-XX(a)(b)(c), UB-IS-XX(a)(b)(c), UB-IS-XX-48V(a)(b)(c), UB-OL-XX-24V(a)(b)(c), UB-OL-XX-48V(a)(b)(c), UB-RS-XX-12V(a)(b)(c), UB-RS-XX-24V(a)(b)(c), UB-RS-XX-48V(a)(b)(c)

Low Voltage Luminaires, LED Flexible Strip, Surface mounted, Class 2 Luminaires, Model(s): CB-DGTL-RGBXX Where XX may be any letters or numbers combination designating LED color, or could be blank to not specify color, may be provided with the prefix "IP" followed by additional numbers when silicone sleeve is provided, may be followed by other suffix to indicate total strip length, may be followed by -12V or -24V indicating input voltage.

Low Voltage Luminaires, LED Flexible Strip, Surface mounted, Class 2 Luminaires, Model(s): CB-RGBDYN-XX Where XX may be any letters or numbers combination designating LED color, or could be blank to not specify color, may be provided with the prefix "IP" followed by additional numbers when silicone sleeve is provided, may be followed by other suffix to indicate total strip length, may be followed by -12V or -24V indicating input voltage

Low Voltage Luminaires, LED Flexible Strip, Surface mounted, Class 2 Luminaires, Model(s): UB-SNA-DWXX Where XX may be any letters or numbers combination designating LED color, or could be blank to not specify color, may be provided with the prefix "IP" followed by additional numbers when silicone sleeve is provided, may be followed by other suffix to indicate total strip length, may be followed by -12V or -24V indicating input voltage.

- (a) - "XX" in the nomenclature may be any letters or numbers combination designating LED color, or could be blank to not specify color.
- (b) - May be provided with the prefix "IP" followed by additional numbers when silicone sleeve is provided.
- (c) - May be followed by other suffix to indicate total strip length.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"